

# Refrigerated Micro Centrifuge

## Digital-20000 R.P.M.(Brushless Motor)

**Laby**™

### PREMIUM MODEL BRUSHLESS



Angle Head 12 x 2ml



Angle Head 24 x 2ml



Model : T-55 BL

### Specifications

- Bench Top high speed Refrigerated Micro Centrifuge Machine
- Heavy duty C.R.C. construction finished with powder coating
- Stainless Steel centrifugal bowl for extra protection and easy cleaning.
- Fitted with well balanced brushless motor with electronic drive.
- 4 lines, 20 characters. LCD Display for set time, run time, set and run rpm, rcf and rotor identification.
- Digital Timer 0-99 minutes, lid lock and fast spin option
- Dynamic brake (automatic) and imbalance detector are provided.
- Selection of 3 acceleration + 4 deceleration profile.
- Microprocessor based. Programmable Speed Regulator from 2000 to 20000 in interval of 100 rpm
- Last test parameter recall and displays automatically on LCD
- P.I.D. Electronic digital temperature controller cum indicator is fitted to control the centrifuge temp. from room temp. upto -20°C means shuts off the cooling compressor within accuracy of + 2°C.
- Supply completed with, instruction manual, cord & plug to work on 220 volts 50Hz A.C.

### Technical Parameter

► Max. Speed	20000 R.P.M.
► Max. RCF	23000xg
► Timer	0-99 Min.
► Motor	Brushless Motor
► Temp. Range	from room temperature- to -20°C
► Temp. Accuracy	±2°C (at 20000 rpm upto 5 minute operation of centrifuge)
► Power	AC 220V 50 Hz 20A
► Weight	55 kg. Approx.
► Dimension	L-25" x W-20" x H-14" approx.

Machine comes without rotor heads.

Optional rotors can be selected as per customer's requirements are as under

Rotor Type	Rotor Capacity	Speed on Rotor (RPM)	R.C.F.
► Angle Rotor	12 x 1.5/2.2 ml.	20000	23000 xg
► Angle Rotor	24 x 1.5/2.2 ml.	16000	18000 xg

- Note: The speed of the machine depends upon the type of rotor being used. If rotor is heavy the speed will reduce as per above